



J300 Specifications

Drive System	Capstan drive
Tracks	2 tracks, 1 channel monophonic
Tape Speed	2.4 cm/ sec., 1.2 cm/ sec. switchable
Microphone Sensitivity	Continuous adjustment using volume knob
Recording Method	n/a
Voice Activation	Continuous adjustment using volume knob in the VCVE (Variable Control Voice Actuator) recording mode
Speaker	28mm diameter dynamic internal speaker
Overall Frequency Response	400 ~ 4,000Hz at 2.4 cm/ sec. 400 ~ 3,000Hz at 1.2 cm/ sec.
Remote Jack	n/a
MIC Jack	2.5 mm diameter, impedance 2k (headphones)
Earphone Jack	2.5 mm diameter, impedance 2k (headphones)
Practical Max Output	150 mW at 2.4 cm/ sec.
Continuous Battery Duration Time	Recording time 17 hours (when alkaline manganese dry cell batteries are used by the Olympus testing method)

Power Source	Rated voltage 3V DC
Battery	Two 1.5V AAA batteries
External Power Supply	A-321 AC Adapter
Dimensions	4.25 in. (L) x 0.75 in. (H) x 2.1 in. (W) / 108 mm (L) x 19 mm (H) x 53 mm (W) (excluding protrusions)
Weight	4.9 oz. / 140 g (including batteries)