

LCR5D ADVOCATE V RECORDER

SPECIFICATIONS

Cassette Type: Standard C90 cassette

Tape Format: Four-channel/single pass

Recording Time: 15/16 IPS, 90 minutes; 15/32 IPS 180 minutes

Fast Forward and Rewind Time: 130 seconds maximum

Power Source/Consumption: 85 ~ 130V 60 Hz 0.8 maximum

Input Impedance: 2.7 Kohm isolation transformer

Frequency Response: 15/16 IPS, 250 Hz - 5 KHz +3/-6 dB; 15/32 IPS, 250 Hz - 2.5 KHz +3/-6 dB

Signal to Noise Ratio: 15/16 IPS 40 dB minimum

15/32 36 dB minimum

Wow and Flutter: 15/16 IPS Maximum 0.4% wtd.

15/32 IPS Max. 0.6% wtd.

Distortion: Max. 3% THD at normal recording level

Signal Input Range: -90 dBm ~ -40 dBm (Input adjustable with gain control per each channel)

AGC Range: 30 dB min.

AGC Attack Time: 5 - 20 msec.

AGC Recovery Time: Approx. 200 ms

Recorder Change Over Time: 3 minutes

Operating Temperature: 0 - 50° C (32 - 122° F)

Operating Humidity: 0-99% relative. with no condensation

Dimensions: 17"W X 7.5"H X 9.4"D Weight: 21 lbs.

Color: Charcoal Gray U.I.. Listed

