



## S711 Specifications

Drive System	Capstan drive
Tracks	2 tracks, 1 channel monophonic
Tape Speed	2.4 cm/ sec., 1.2 cm/ sec. switchable
Microphone Sensitivity	Continuous adjustment using volume knob
Recording Method	n/a
Voice Activation	Continuous adjustment using volume knob in the VCVE (Variable Control Voice Actuator) recording mode
Speaker	36 mm dynamic internal speaker
Overall Frequency Response	400 ~ 4,000Hz at 2.4 cm/ sec. 400 ~ 3,000Hz at 1.2 cm/ sec.
Remote Jack	n/a
MIC Jack	2.5 mm diameter, impedance 2k ohms
Earphone Jack	2.5 mm diameter, impedance 8 ohms
Practical Max Output	150 mW at 2.4 cm/ sec.
Continuous Battery Duration Time	Recording time 17 hours (when alkaline manganese dry cell batteries are used by the Olympus testing method)

Power Source	n/a
Battery	Two 1.5V AA batteries
External Power Supply	A-321 AC Adapter
Dimensions	4.8 in. (L) x 1.0 in. (H) x 2.3 in. (W) / 121 mm (L) x 26 mm (H) x 58 mm (W) (excluding protrusions)
Weight	5.6 oz. / 160 g (including batteries)
Drive System	Capstan drive
Tracks	2 tracks, 1 channel monophonic
Tape Speed	2.4 cm/ sec., 1.2 cm/ sec. switchable
Microphone Sensitivity	Continuous adjustment using volume knob
Recording Method	n/a
Voice Activation	Continuous adjustment using volume knob in the VCVE (Variable Control Voice Actuator) recording mode
Speaker	36 mm dynamic internal speaker
Overall Frequency Response	400 ~ 4,000Hz at 2.4 cm/ sec. 400 ~ 3,000Hz at 1.2 cm/ sec.
Remote Jack	n/a
MIC Jack	2.5 mm diameter, impedance 2k ohms
Earphone Jack	2.5 mm diameter, impedance 8 ohms

**Practical Max Output** 150 mW at 2.4 cm/ sec.

**Continuous Battery Duration Time** Recording time 17 hours (when alkaline manganese dry cell batteries are used by the Olympus testing method)

**Power Source** n/a

**Battery** Two 1.5V AA batteries